

sunwins

Portable Ventilator



Performance introduction

The Portable high-speed ventilator, movable ventilator is blessed with low power consumption, large wind volume, high wind pressure and low noise and so on, moreover it is reasonably structured and conveniently applied. Its surface is clean, bright and durable after advanced spraying process. It has been widely used for ventilation in warehouses, basements, car parks, manhole, tunnels and other places.

SPEFICATION

Item	Size	Voltage	Phase	Frequency	Power	Air Volume	Pressure	Noise	Speed	Weight
Model	mm/inch	(V)		HZ	(W)	(m3/min)	Pa	dBA	R.P.M	KG
SP 30	300/12	240	1	50	520	65	370	69	2900	11
SP 40	400/16	240	1	50	1100	105	700	79	2900	24
SP 40	400/16	415	3	50	1100	105	700	79	2900	24
SP 45	450/18	240	1	50	700	110	350	70	1400	29
SP 45	450/18	415	3	50	700	110	350	70	1400	29
SP 50	500/20	240	1	50	1100	150	400	73	1400	40
SP 50	500/20	415	3	50	1100	150	400	73	1400	40
SP 60	600/24	415	1	50	1800	240	480	77	1400	78
SP 60	600/24	415	3	50	1800	240	480	77	1400	78

sunwins

Flexible Duct Hose



PVC water and fire resistant fabric

Temperature range -20-80°C.

Supported by helix steel wire and black rubber strip, it is wear-and-tear proof

Normal production: one end with bugle and rope, one end with metal ring

With hanging rings every 1 meter

Standard diameter: 200mm-600mm,

Standard length: 5m

Custom sizes are available upon requests.

Packing: Neutral carton packing

Color : Orange